41593 Winchester Road, #200
Temecula, California, USA 92592
Ph: 951.526.2239 | Fax: 951.526.2441
www.srsintldirect.com

Electromagnetic flowmeter

- Electrode material :316L or customize
- Lining material :PTFE or customize
- Shell material :carbon steel
- Type : remote type or integrated type (option)

Type choosing

iameter (mm)	Measure range (m3/h)	Range within accuracy (m3/h)	DN (mm)	Measure range (m3/h)	Range within accuracy (m3/h)
DN10	0.014~3.39	0.08~2.82	DN 300	12.7~3052	76~2543
DN 15	0.03~7.63	0.19~6.35	DN 350	17.3~4154	103~3461
DN 20	0.06~13.56	0.33~11.34	DN 400	22.6~5425	1355~4521
DN 25	0.09~21.19	0.52~17.66	DN 450	28.6~6867	171~5722
DN 32	0.14~34.72	0.86~29.93	DN 500	35.3~8478	211~7065
DN 40	0.23~54.25	1.35~45.21	DN 600	51~12208	305~10173
DN 50	0.35~84.78	2.12~70.65	DN 700	69~16616	415~13847
DN 65	0.6~143	3.58~119	DN 800	90~21703	542~18086
DN 80	0.90~217	5.43~180	DN 900	114~27468	686~22890
DN 100	1.41~339	8.48~282	DN 1000	141~33912	847~28260
DN 125	2.21~529	13.25~441	DN 1200	203~48833	1221~40694
DN 150	3.18~763	19.08~635	DN 1400	277~66467	1662~55389
DN 200	5.65~1356	33.91~1130	DN 1600	361~86814	2171~72345
DN 250	8.83~2119	52.99~1766	DN 1800	457~109874	2747~91562

Electromagnetic flowmeter selection of samples

SRS-EMFM□ □ □ □ □ □ □ □ □ □

- SRS-EMFM: Electromagnetic flow meter
- Caliber: 10,15,20,25,32,40,50,65,80,100,125,150,200,250,300,350,400,450,500,600,700,800,1000,1200，1400,1600,1800
- Body material: CS-carbon steel; 304-SS304; 316L-SS316
- Lining material: L1-PTFE; L2-rubber; L3-PFA; L4- Polyurethane
- Electrode material: EN-316L; Hc- Hastelloy alloy C; Hb- Hastelloy alloy B; Ta- Tantalum; Ti-Titanium; Pt-Platinum
- Output: N - 4-20 Ma+pulse; H - Hart; R-RS485
- Power supply: A-220V; D-24V; B-Battery
- Structure: I-Integrated type; R-Remote type
- IP Rating: Ip65; IP68
- Grounding ring: GR

Products Detail